

## Data Sheet

# Danfoss Link™ RS - Room Sensor

### Application



Danfoss Link™ RS - Room Sensor is an electronic sensor for measuring room temperature.

The Room Sensor is a part of the Danfoss Link™ system, which is used for wireless linking and controlling of heating systems in residential and light commercial buildings.

The Danfoss Link™ RS - Room Sensor has a built-in temperature sensor, which measures the ambient temperature. It allows you to control the heating, based on room temperature in the room where installed. With the Danfoss Link™ RS you can also adjust the requested temperature.

### Ordering

Product	Code no.
Danfoss Link™ RS - Room Sensor	014G0158

### Technical Data

Battery	2x1.5V AA alkaline
Battery life	Up to 4-5 years
Backlight	White LED
Battery level	Indication in display
Ambient temperature	0° to +40°C
Transmission frequency	868.42 MHz
Transmission range in normal buildings	Up to 30 m
Transmission power	Max. 1 mW
IP class	21
Dimensions	76 mm x 76 mm x 23 mm

Danfoss A/S  
Heating Solutions  
Haarupvaenget 11  
8600 Silkeborg  
Denmark  
Phone: +45 7488 8000  
Fax: +45 7488 8100  
Email: [heating.solutions@danfoss.com](mailto:heating.solutions@danfoss.com)  
[www.heating.danfoss.com](http://www.heating.danfoss.com)

---

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---